LIXADEIRA VIBRATÓRIA GSS 140

SKU	0601.2A8.0K0-UUU



Conteúdo da Embalagem

3 folhas de lixa C470, Best for Wood + Paint, 80 (disponíveis em separado como conjunto de 5: 2 608 605 069)	✓
Caixa de cartão	✓

Technical Data

Weight	1,200 kg
No-load speed	14,0 r.p.m.
No-load speed, up to	14.000,0 r.p.m.
Rated input power	220,0 W
Orbit diameter	1,500 mm
No-load orbital stroke rate	28,0 o.p.m.
No-load orbital stroke rate, up to	28.000,0 o.p.m.
Phase Out Date	14.05.2024
Uncertainty K	3,0 dB
Sound pressure level	79,0 dB(A)
Noise level	O nível sonoro da ferramenta eléctrica classificado com A é normalmente: nível de pressão sonora 79 dB(A); nível de potência sonora dB(A). Incerteza K= 3 dB.
Total vibration values	1,500 Lixar material em placas 7,0
Net Weight	1,180 kg
Gross Weight	1,380 kg

Origem do material	China

Product Benefits

- Flexível e sem fadiga para longas horas de trabalho mesmo para operações acima do nível da cabeça
- Ótimo design ergonómico com opções múltiplas de fixação
- Vibrações e peso reduzidos